

Tabla de especificaciones para tubería de acero sin soldadura

Tubos sin soldadura										
DIN 2448/81										
e (mm)		2,9	3,2	3,6	4	4,5	5	5,6	6,3	7,1
∅ (mm)	∅ (pulg)	Peso (kg/m)								
60,3	2"	4,11								
88,9	3"		6,76	7,57						
114,3	4"			9,83	10,90					
139,7	5"				13,40	15,00				
168,3	6"					18,20	20,10	22,50		
219,1	8"								33,10	
273,0	10"								41,40	
323,9	12"									55,50

Tubos sin soldadura acero al carbono				DIN 2440/78	
Paso nominal	ø ext. (mm)	e (mm)	Peso (kg/m)	Tolerancias de ø	
				Máx. mm	Mín. mm
1/8	10,20	2,00	0,407	10,60	9,80
1/4	13,50	2,35	0,650	14	13,20
3/8	17,20	2,35	0,852	17,50	16,70
1/2	21,30	2,65	1,220	21,80	21,00
3/4	26,90	2,65	1,580	27,30	26,50
1	33,70	3,25	2,440	34,20	33,30
1 1/4	42,40	3,25	3,140	42,90	42,00
1 1/2	48,30	3,25	3,610	48,80	47,90
2	60,30	3,65	5,100	60,80	59,70
2 1/2	76,10	3,65	6,510	76,60	75,3
3	88,90	4,05	8,470	89,50	88
3 1/2	101,60	4,05	9,720	102,10	100,4
4	114,30	4,50	12,100	115,00	113,1
5	139,70	4,85	16,200	140,80	138,5
6	165,10	4,85	19,200	166,50	163,9

Tubos sin soldadura acero al carbono				DIN 2440/78	
Paso nominal	ø ext. (mm)	e (mm)	Peso (kg/m)	Tolerancias de ø	
				Máx. mm	Mín. mm
1/8	10,20	2,65	0,493	10,60	9,80
1/4	13,50	2,90	0,769	14	13,20
3/8	17,20	2,90	1,020	17,50	16,70
1/2	21,30	3,25	1,450	21,80	21,00
3/4	26,90	3,25	1,900	27,30	26,50
1	33,70	4,05	2,970	34,20	33,30
1 1/4	42,40	4,05	3,840	42,90	42,00
1 1/2	48,30	4,05	4,430	48,80	47,90
2	60,30	4,50	6,170	60,80	59,70
2 1/2	76,10	4,50	7,900	76,60	75,3
3	88,90	4,85	10,100	89,50	88
3 1/2	101,60	4,85	11,600	102,10	100,4
4	114,30	5,40	14,400	115,00	113,1
5	139,70	5,40	17,800	140,80	138,5
6	165,10	5,40	21,200	166,50	163,9